

## USAGE AND TECHNICAL DATA SHEET

# **SUPER UNIVERSAL CLEANER**

(75-32)

RECOMMENDED FOR USE AT A 40-1 DILUTION.

### FOR USE ON;

TARPAULINS  
METALS  
FIREPLACES  
MACHINERY  
PLASTIC FURNITURE  
FLOOR COVERINGS

### EFFECTIVE REMOVAL OF;

SOOT  
CARBON RESIDUE  
OIL  
GREASE  
RESINS  
DYES  
NICOTINE  
MILDEW  
INDUSTRIAL DIRT RESIDUALS

### PROPERTIES;

LEAVES NO RESIDUE PRIOR TO PAINTING  
(FLUSH SURFACE WITH WATER BEFORE POWDER COATING)  
SUBSTITUTES ORGANIC THINNERS AND AMMONIUM CHLORIDE  
FAST ACTING  
LOW FOAMING  
EMUSIFIABLE  
ACID FREE  
NON COMBUSTIBLE  
NEUTRAL ODOUR  
SENSITIVE TO FREEZING, STORE AT ROOM TEMPERATURE.  
CAN BE USED NEAT  
CAN BE USED IN HIGH PRESSURE CLEANING  
CAN BE SAFELY USED IN FOOD PREPARATION AREAS.

PLEASE TEST COMPATIBILITY BEFORE USE ON ZINC OR ALUMINIUM COATINGS.